

Catalogue No: **1606-XLS240-UPS**

UPS CHARGING MODULE 22.5-30VDC TO 22.5VDC 240W 10A

Power Distribution and Protection > Power Supplies and Transformers > Switched Mode Power Supplies > Allen-Bradley Switched Mode Power Supplies > 1606-XLS Performance Series > 1606-XLS Performance Specialty Modules



Representative Photo Only
(actual product may vary based on configuration selections)

Power supply, 240 W, 10 A w/UPS

- Efficient power supplies which minimise heat output and reduce associated running costs
- Redundancy module options allow for backup power in critical applications
- The compact footprint maximises usable space with the panel

HighFive PLC

sales@5gplc.com

+86 13306036024

SPECIFICATIONS	
Product Series	Bul. 1606-XLS
Component Type Power Distribution & Protection	Switched Mode Power Supply
Input Type	DC
Input Voltage, DC, Min	22.5 V DC min
Input Voltage, DC, Max	30 V DC max
In, Nominal Current	10 A
Inrush Current, Max	0.0013 A
Un, Nominal Voltage, AC, L-L	230 V AC
Indicator Type	LED
Output Voltage, DC, Nom	24 V DC
Output Current, Rated (rms)	10 A
Pout, Real, Rated W	240 W
MTBF, Mean Time Before Failure, Min	886000 hours
Mounting	DIN-35 Rail Mount
IP Rating	IP20
Height	124 mm
Width	49 mm
Depth	117 mm
Weight	0.53 kg
Standards Compliance	UL 508 IEC 60950 EN 60950 EN 50178
Certifications	CE

Catalogue No: **1606-XLS240-UPS**

UPS CHARGING MODULE 22.5-30VDC TO 22.5VDC 240W 10A

Power Distribution and Protection > Power Supplies and Transformers > Switched Mode Power Supplies > Allen-Bradley Switched Mode Power Supplies > 1606-XLS Performance Series > 1606-XLS Performance Specialty Modules



REFERENCES

IECEX Certificate -

Supplier Declaration of Conformity: -

Installation Guide: -

User Manual -

Manufacturer Datasheet: -

Manufacturer Catalogue & Product Selection: -

HighFive PLC

sales@5gplc.com

+86 13306036024